



Pafra Adhesives Ltd  
Bentalls, Basildon,  
Essex, SS14 3BU

Telephone +44 (0) 1268 290610  
Fax +44 (0) 1268 290619  
Email [enquiries@pafra.com](mailto:enquiries@pafra.com)  
Website [www.pafra.com](http://www.pafra.com)

## AquaPAL® 9278 Premium Jetting Adhesive

Issue 6 05/06/2017

AquaPAL® 9278 is a premium jetting adhesive specifically developed for the carton converting and corrugated packaging markets. It contains an additive so that it can be picked up by UV detection equipment.

AquaPAL® 9278 offers exceptional clean running, and is very resistant to drying on nozzle tips. This is especially useful with multi-gun arrangements.

AquaPAL® 9278 gives an excellent bond to both plain and coated boards. It can be used to gain deeper fiber tear with Kraft liner paper or where clay coat stripping is a problem.

### Features & Benefits

- Exceptional clean running
- Excellent bond to difficult liner papers and coated boards
- Supreme spotting and lining performance
- High penetration for clay coated boards

### Technical Data

<b>Viscosity:</b>	1.60-2.10 Poise @ 125.0 sec <sup>-1</sup>	<b>pH:</b>	~4.6
<b>Solids:</b>	46.0 - 49.0%	<b>sg (20 °C)</b>	1.07
Brookfield 2/20/25:	360 centiPoise	<b>Colour:</b>	White

### Application Details

AquaPAL® 9278 is designed specifically for use in low pressure jetting systems and WH Leary high pressure systems.

### Storage & Shelf Life

For optimum performance use within 6 Months. Store between 5-30 °C and protect from freezing. Stir or shake before use.

### Health & Safety

Users should familiarise themselves with the safety data sheet before using or handling this product.

### Regulatory

Every precaution has been taken in the design of this adhesive to ensure it safe for the consumer.

Tel: 01 – 885 00 00

[www.ect.ie](http://www.ect.ie)

[info@ect.ie](mailto:info@ect.ie)

Recommendations and suggestions for the use of our materials are based on our best experience and knowledge and intended to serve as a guide only. Customers should satisfy themselves by appropriate trials that products are suitable for their applications. The Pafra Adhesives logo, AquaPAL® and ThermoPAL® are all trademarks of Pafra Adhesives Ltd.



Pafra Adhesives Ltd's registered office: 145-147 St John Street, London, EC1V 4PY.  
The Company is registered in England: No.644949 and for VAT, registration: No. GB 250 4895 54